

# Sigen LoadHub

- 5 double-pole controllable loads
- 0 ms load-side disruption when switching to backup mode
- Supports generator, heat pump or other controllable load
- Supports both whole-home & partial-home backup
- Uninterrupted power supply through PV +ESS/grid/generator



# Sigen LoadHub

Sigen LoadHub		Units
<b>Electrical Specification</b>		
Grid connection type	Split phase	
Nominal AC voltage	120 / 240	V
Nominal AC frequency	60	Hz
Max. short circuit current ( I <sub>sc</sub> )	10	kA
Current measurement accuracy	≤ 1 %	
Voltage measurement accuracy	≤ 1 %	
<b>Grid Connection</b>		
Max. continuous current	200	A
Max. overcurrent protection device rating	200	A
Disruption time of backup switchover <sup>1,2</sup>	0	ms
<b>AC Output to Main Distribution Panel</b>		
Max. continuous current	200	A
Max. overcurrent protection device rating	200	A
Overvoltage category	IV	
<b>SigenStor Connection</b>		
Max. number of connection	2	
Max. continuous current	48	A
Max. overcurrent protection device rating	60	A
Max. AC nominal power per inverter connection	11.5	kW
<b>Smart Load Port Connection</b>		
Max. number of connection	5	
Max. continuous current	64	A
Max. overcurrent protection device rating	80	A
<b>Generator Port Connection</b>		
Max. continuous current	64	A
Max. overcurrent protection device rating	80	A
Dry contact switch voltage rating	30	V
Dry contact switch current rating	1	A
Generator 2-wire start	Supported	
<b>General Data</b>		
Dimensions (W / H / D)	21 x 32 x 7 / 532 x 814 x 180	in / mm
Weight	60 / 27	lbs / kg
Storage temperature range	-40 ~ 158 / -40 ~ 70	°F / °C
Operating temperature range	-22 ~ 131 / -30 ~ 55	°F / °C
Relative humidity range	0% ~ 95%	
Max. operating altitude	13123 / 4000	ft / m
Cooling	Natural convection	
Enclosure type	Type 3R	
Communication	Fast Ethernet (FE), RS485, dry contact	
Installation method	Wall-mounted	
<b>Standard Compliance</b>		
Certifications	FCC Part 15 Subpart B, ICES-003, ANSI C63.4a:2017, UL 67, UL 869A UL 1741, UL 1741 PCS CRD, CSA C22.2 No.107.1-16, CA Proposition 65	

1. This refers to the load-side disruption time, to achieve this function Sigen LoadHub needs to be used together with Sigen Energy Controller US and Sigen Battery US. Test conditions: In the open-circuit state of the power grid, the nominal power of the Sigen Energy Controller US is higher than the total power of the home loads.
2. The MID Switch complies with UL Category NRNT2 and fulfills with the standards of UL 508, UL 60947-1, UL 60947-4-1, UL 61810-1 as well as UL 61810-20.

Disclaimer: The information in this file is provided on an "as is" basis. To the fullest extent permitted by law, Sigen Technology Co., Ltd. excludes all representations and warranties relating to this file and its contents or which is or may be provided by any affiliates or any other third party, including in relation to any inaccuracies or omissions in this file.