



## KD 200-60 F Series

KD240GX-LFB2

KD245GX-LFB2

KD250GX-LFB2

### CUTTING EDGE TECHNOLOGY

As a pioneer with over 35 years in the solar energy industry, Kyocera demonstrates leadership in the development of solar energy products. Kyocera's *Kaizen* Philosophy, commitment to continuous improvement, is shown by repeatedly achieving world record cell efficiencies.

### QUALITY BUILT IN

- UV stabilized, aesthetically pleasing black anodized frame
- Supported by major mounting structure manufacturers
- Easily accessible grounding points on all four corners for fast installation
- Proven junction box technology with 12 AWG PV wire to work with transformerless inverters
- Quality locking plug-in connectors to provide safe and quick connections

### RELIABLE

- Proven superior field performance
- Tight power tolerance
- Only module manufacturer to pass rigorous long-term testing performed by TÜV Rheinland



### QUALIFICATIONS AND CERTIFICATIONS

UL Listing  
QIGU.E173074



NEC 2008 Compliant, UL 1703, and ISO 14001

UL1703 Certified and Registered, UL Fire Safety Class C, CEC, FSEC

## ELECTRICAL SPECIFICATIONS

Standard Test Conditions (STC) <i>STC = 1000 W/M<sup>2</sup> irradiance, 25°C module temperature, AM 1.5 spectrum*</i>				
	KD240GX-LFB2	KD245GX-LFB2	KD250GX-LFB2	
P <sub>mp</sub>	240	245	250	W
V <sub>mp</sub>	29.8	29.8	29.8	V
I <sub>mp</sub>	8.06	8.23	8.39	A
V <sub>oc</sub>	36.9	36.9	36.9	V
I <sub>sc</sub>	8.59	8.91	9.09	A
P <sub>tolerance</sub>	+5/-3	+5/-3	+5/-3	%


Nominal Operating Cell Temperature Conditions (NOCT) <i>NOCT = 800 W/M<sup>2</sup> irradiance, 20°C ambient temperature, AM 1.5 spectrum*</i>				
	KD240GX-LFB2	KD245GX-LFB2	KD250GX-LFB2	
T <sub>NOCT</sub>	45	45	45	°C
P <sub>max</sub>	172	176	180	W
V <sub>mp</sub>	26.7	26.8	26.8	V
I <sub>mp</sub>	6.45	6.58	6.72	A
V <sub>oc</sub>	33.7	33.7	33.7	V
I <sub>sc</sub>	6.95	7.21	7.36	A
PTC	217.3	219.1	223.7	W

Temperature Coefficients				
P <sub>max</sub>	-0.46	-0.46	-0.46	%/°C
V <sub>mp</sub>	-0.52	-0.52	-0.52	%/°C
I <sub>mp</sub>	0.0064	0.0065	0.0065	%/°C
V <sub>oc</sub>	-0.36	-0.36	-0.36	%/°C
I <sub>sc</sub>	0.060	0.060	0.060	%/°C
Operating Temp	-40 to +90	-40 to +90	-40 to +90	°C

System Design	
Series Fuse Rating	15 A
Maximum DC System Voltage (UL)	600 V
Hailstone Impact	1 in (25mm) @ 51mph (23m/s)

\* Subject to simulator measurement uncertainty of +/- 3%. KYOCERA reserves the right to modify these specifications without notice.

NEC 2008 COMPLIANT  
UL 1703 LISTED



## MODULE CHARACTERISTICS

Dimensions: <i>length/width/height</i>	65.43in/38.98in/1.81in (1662mm/990mm/46mm)
Weight:	44.1lbs (20.0kg)

## PACKAGING SPECIFICATIONS

Modules per pallet:	20
Pallets per 53' container:	36
Pallet box dimensions: <i>length/width/height</i>	66in/40in/47in (1675mm/1005mm/1175mm)
Pallet box weight:	990 lbs (450kg)

