



KD 200-60 F Series

KD240GX-LFB2

KD245GX-LFB2

KD250GX-LFB2

CUTTING EDGE TECHNOLOGY

As a pioneer with over 35 years in the solar energy industry, Kyocera demonstrates leadership in the development of solar energy products. Kyocera's *Kaizen* Philosophy, commitment to continuous improvement, is shown by repeatedly achieving world record cell efficiencies.

QUALITY BUILT IN

- UV stabilized, aesthetically pleasing black anodized frame
- Supported by major mounting structure manufacturers
- Easily accessible grounding points on all four corners for fast installation
- Proven junction box technology with 12 AWG PV wire to work with transformerless inverters
- Quality locking plug-in connectors to provide safe and quick connections

RELIABLE

- Proven superior field performance
- Tight power tolerance
- Only module manufacturer to pass rigorous long-term testing performed by TÜV Rheinland



QUALIFICATIONS AND CERTIFICATIONS

UL Listing
QIGU.E173074



NEC 2008 Compliant, UL 1703, and ISO 14001

UL1703 Certified and Registered, UL Fire Safety Class C, CEC, FSEC

ELECTRICAL SPECIFICATIONS

Standard Test Conditions (STC)
*STC = 1000 W/M² irradiance, 25°C module temperature, AM 1.5 spectrum**

	KD240GX-LFB2	KD245GX-LFB2	KD250GX-LFB2	
P_{mp}	240	245	250	W
V_{mp}	29.8	29.8	29.8	V
I_{mp}	8.06	8.23	8.39	A
V_{oc}	36.9	36.9	36.9	V
I_{sc}	8.59	8.91	9.09	A
P_{tolerance}	+5/-3	+5/-3	+5/-3	%

Nominal Operating Cell Temperature Conditions (NOCT)
*NOCT = 800 W/M² irradiance, 20°C ambient temperature, AM 1.5 spectrum**

T_{NOCT}	45	45	°C
P_{max}	172	176	W
V_{mp}	26.7	26.8	V
I_{mp}	6.45	6.58	A
V_{oc}	33.7	33.7	V
I_{sc}	6.95	7.21	A
PTC	217.3	219.1	W

Temperature Coefficients


P_{max}	-0.46	-0.46	-0.46	%/°C
V_{mp}	-0.52	-0.52	-0.52	%/°C
I_{mp}	0.0064	0.0065	0.0065	%/°C
V_{oc}	-0.36	-0.36	-0.36	%/°C
I_{sc}	0.060	0.060	0.060	%/°C
Operating Temp	-40 to +90	-40 to +90	-40 to +90	°C

System Design

Series Fuse Rating	15 A
Maximum DC System Voltage (UL)	600 V
Hailstone Impact	1 in (25mm) @ 51mph (23m/s)

* Subject to simulator measurement uncertainty of +/- 3%.
 KYOCERA reserves the right to modify these specifications without notice.

NEC 2008 COMPLIANT
 UL 1703 LISTED



MODULE CHARACTERISTICS

Dimensions: 65.43in/38.98in/1.8in
length/width/height

Weight: 44.1lbs (20.0kg)

PACKAGING SPECIFICATIONS

Modules per pallet: 20

Pallets per 53' container: 36

Pallet box dimensions: 66in/40in/47in
length/width/height

Pallet box weight: 990 lbs (450kg)

