

Innovation for a Better Life



LG305N1K-G4

60 cell

LG's new module, LG NeON[™] 2 Black, adopts Cello technology. Cello technology replaces 3 busbars with 12 thin wires to enhance power output and reliability. LG NeON[™] 2 Black demonstrates LG's efforts to increase customer's values beyond efficiency. It features enhanced warranty, durability, performance under real environment, and aesthetic design suitable for roofs.







Enhanced Performance Warranty

LG NeON[™] 2 Black has an enhanced performance warranty. The annual degradation has fallen from -0.7%/yr to -0.6%/yr. Even after 25 years, the cell guarantees 2.4%p more output than the previous LG NeON[™] modules.



Aesthetic Roof

LG NeON^m 2 Black has been designed with aesthetics in mind; thinner wires that appear all black at a distance. The product may increase the value of a property with its modern design.



Better Performance on a Sunny Day

LG NeONTM 2 Black now performs better on sunny days thanks to its improved temperature coefficiency.



High Power Output

Compared with previous models, the LG NeON™ 2 Black has been designed to significantly enhance its output efficiency, thereby making it efficient even in limited space.



Outstanding Durability

With its newly reinforced frame design, LG has extended the warranty of the LG NeON[™] 2 Black for an additional 2 years. Additionally, LG NeON[™] 2 Black can endure a front load up to 6000 Pa, and a rear load up to 5400 Pa.



The rear of the cell used in LG NeON™ 2 Black will contribute to generation, just like the front; the light beam reflected from the rear of the module is reabsorbed to generate a great amount of additional power.

About LG Electronics

LG Electronics is a global player who has been committed to expanding its capacity, based on solar energy business as its future growth engine. We embarked on a solar energy source research program in 1985, supported by LG Group's rich experience in semi-conductor, LCD, chemistry, and materials industry. We successfully released first Mono X[®] series to the market in 2010, which were exported to 32 countries in the following 2 years, thereafter. In 2013, NeONTM (previously known as Mono X[®] NeON) & 2015 NeON2 with CELLO technology won "Intersolar Award", which proved LG is the leader of innovation in the industry.

$LG N_{e} O N^{M} 2Black$

LG305N1K-G4

Mechanical Properties

Cells	6 x 10
Cell Vendor	LG
Cell Type	Monocrystalline / N-type
Cell Dimensions	156.75 x 156.75 mm / 6 inches
# of Busbar	12 (Multi Wire Busbar) 攀
Dimensions (L x W x H)	1640 x 1000 x 40 mm
	64.57 x 39.37 x 1.57 inch
Front Load	6000 Pa / 125 psf 🐡
Rear Load	5400 Pa / 113 psf 🐡
Weight	17.0 ± 0.5 kg / 37.48 ± 1.1 lbs
Connector Type	MC4, MC4 Compatible, IP67
Junction Box	IP67 with 3 Bypass Diodes
Length of Cables	2 x 1000 mm / 2 x 39.37 inch
Glass	High Transmission Tempered Glass
Frame	Anodized Aluminum

Certifications and Warranty

Certifications	IEC 61215, IEC 61730-1/-2
	IEC 62716 (Ammonia Test)
	IEC 61701 (Salt Mist Corrosion Test)
	ISO 9001
	UL 1703
Module Fire Performance (USA)	Type 2 (UL 1703)
Fire Rating (for CANADA)	Class C (ULC/ORD C1703)
Product Warranty	12 years 🐡
Output Warranty of Pmax	Linear warranty* 🌞

* 1) 1st year. 98%, 2) After 2nd year. 0.6%p annual degradation, 3) 83.6% for 25 years


Temperature Characteristics

NOCT	45 ± 3 ℃
Ртрр	-0.38 %/°C 🐡
Voc	-0.28 %/°C
lsc	0.03 %/°C

Characteristic Curves

G

Life's Good



Electrical Properties (STC *)

Module Type	305 W	
MPP Voltage (Vmpp)	32.9	
MPP Current (Impp)	9.28	
Open Circuit Voltage (Voc)	40.1	
Short Circuit Current (Isc)	9.74	
Module Efficiency (%)	18.6	
Operating Temperature (°C)	-40 ~ +90	
Maximum System Voltage (V)	1000 (IEC/UL)	
Maximum Series Fuse Rating (A)	20	
Power Tolerance (%)	0 ~ +3	


* STC (Standard Test Condition). Irradiance 1000 W/m², Module Temperature 25 °C, AM 1.5
* The nameplate power output is measured and determined by LG Electronics at its sole and absolute discretion.
* The typical change in module efficiency at 200 W/m² in relation to 1000 W/m² is -3.0%.

Electrical Properties (NOCT*)

Module Type	305 W
Maximum Power (Pmax)	225
MPP Voltage (Vmpp)	30.4
MPP Current (Impp)	7.39
Open Circuit Voltage (Voc)	37.3
Short Circuit Current (Isc)	7.84

* NOCT (Nominal Operating Cell Temperature): Irradiance 800 W/m², ambient temperature 20 °C, wind speed 1 m/s

Dimensions (mm/in)



Product specifications are subject to change without notice. DS-N2-60-K-G-F-EN-50427

Copyright © 2016 LG Electronics. All rights reserved. 01/01/2016

Innovation for a Better Life



Contact: lg.solar@lge.com www.lgsolarusa.com

North America Solar Business Team

LG Electronics U.S.A. Inc 1000 Sylvan Ave, Englewood Cliffs, NJ 07632