

SUNNY TRIPOWER

12000TL-US / 15000TL-US / 20000TL-US / 24000TL-US



Design flexibility

- 1000 V DC or 600 V DC
- Two independent DC inputs
- 15° to 90° mounting angle range
- Detachable DC Connection Unit

System efficiency

- 98% CEC, 98.5% Peak
- 1000 V DC increases system efficiency
- OptiTrac advanced MPPT
- OptiTrac Global Peak MPPT

Enhanced safety

- Integrated DC AFCI
- Floating system with all-pole sensitive ground fault protection
- Reverse polarity indicator

Future-proof

- Complete grid management feature set
- Cluster Controller, WebConnect/Speedwire
- Bi-directional Ethernet communications
- Ability to satisfy future utility requirements


SUNNY TRIPOWER

12000TL-US / 15000TL-US / 20000TL-US / 24000TL-US

The ultimate solution for decentralized PV plants

The world's best-selling three-phase PV inverter, the SMA Sunny Tripower TL-US, is raising the bar for decentralized commercial PV systems. This three-phase, transformerless inverter is UL listed for up to 1000 V DC maximum system voltage and has a peak efficiency above 98 percent, while OptiTrac Global Peak minimizes the effects of shade for maximum energy production. The Sunny Tripower delivers a future-proof solution with full grid management functionality, cutting edge communications and advanced monitoring. The Sunny Tripower is also equipped with all-pole ground fault protection and integrated AFCI for a safe, reliable solution. It offers unmatched flexibility with a wide input voltage range and two independent MPP trackers. Suitable for both 600 V DC and 1,000 V DC applications, the Sunny Tripower allows for flexible design and a lower levelized cost of energy.





Accessories



RS485 interface
DM-485CB-US-10



SMA Cluster Controller
CLCON-10



Connection Unit
CU 1000-US-10

- Standard features
 - Optional features
 - Not available
- Data at nominal conditions

Technical data	Sunny Tripower 12000TL-US	Sunny Tripower 15000TL-US	Sunny Tripower 20000TL-US	Sunny Tripower 24000TL-US
Input (DC)				
Max. usable DC power (@ cos φ = 1)	12250 W	15300 W	20400 W	24500 W
Max. DC voltage*	1000 V	1000 V	1000 V	1000 V
Rated MPPT voltage range	300 V...800 V	300 V...800 V	380 V...800 V	450 V...800 V
MPPT operating voltage range	150 V...1000 V	150 V...1000 V	150 V...1000 V	150 V...1000 V
Min. DC voltage / start voltage	150 V / 188 V	150 V / 188 V	150 V / 188 V	150 V / 188 V
Number of MPP tracker inputs	2	2	2	2
Max. input current / per MPP tracker input	66 A / 33 A	66 A / 33 A	66 A / 33 A	66 A / 33 A
Output (AC)				
AC nominal power	12000 W	15000 W	20000 W	24000 W
Max. AC apparent power	12000 VA	15000 VA	20000 VA	24000 VA
Output phases / line connections	3 / 3-N-PE			
Nominal AC voltage	480 / 277 V WYE			
AC voltage range	244 V...305 V			
Rated AC grid frequency	60 Hz			
AC grid frequency / range	50 Hz, 60 Hz / -6 Hz...+5 Hz			
Max. output current	14.4 A	18 A	24 A	29 A
Power factor at rated power / adjustable displacement	1 / 0.8 leading...0.8 lagging			
Harmonics	< 3 %			
Efficiency				
Max. efficiency	98.2 %	98.2 %	98.5 %	98.5 %
CEC efficiency	97.5%	97.5%	97.5%	98.0%
Protection devices				
DC reverse polarity protection	●	●	●	●
Ground fault monitoring / Grid monitoring	●	●	●	●
All-pole sensitive residual current monitoring unit	●	●	●	●
DC AFCI compliant to UL 1699B	●	●	●	●
AC short circuit protection	●	●	●	●
Protection class / overvoltage category	I / IV	I / IV	I / IV	I / IV
General data				
Dimensions (W / H / D) in mm (in)	665 / 690 / 265 (26.1 / 27.1 / 10.4)			
Packing dimensions (W / H / D) in mm (in)	780 / 790 / 380 (30.7 / 31.1 / 15.0)			
Weight	55 kg (121 lbs)			
Packing weight	61 kg (134.5 lbs)			
Operating temperature range	-25 °C...+60 °C			
Noise emission (typical)	51 dB(A)			
Internal consumption at night	1 W			
Topology	Transformerless			
Cooling concept	OptiCool			
Electronics protection rating	NEMA 3R			
Features				
Display / LED indicators (Status / Fault / Communication)	- / ●	- / ●	- / ●	- / ●
Interfaces: Speedwire / RS485	● / ○	● / ○	● / ○	● / ○
Mounting angle range	15°...90°	15°...90°	15°...90°	15°...90°
Warranty: 10 / 15 / 20 years	● / ○ / ○	● / ○ / ○	● / ○ / ○	● / ○ / ○
Certifications and approvals	UL 1741, UL 1998, UL 1699B, IEEE 1547, FCC Part 15 (Class A & B), CAN/CSA C22.2 107.1-1			
NOTE: US inverters ship with gray lids				
*Suitable for 600 V DC max. systems				
Type designation	STP 12000TL-US-10	STP 15000TL-US-10	STP 20000TL-US-10	STP 24000TL-US-10

STP12-US1224-DUS143110 SMA and Sunny Tripower are registered trademarks of SMA Solar Technology AG. Printed on FSC-certified paper. All products and services described as well as technical data are subject to change, even for country-specific deviations, at any time without notice. SMA assumes no liability for errors or omissions. For current information, see www.SMA-Solar.com.